

# 2D Barcode Scanner



## XL-3200



- ⊙ Affordable withstand 1.2m drops
- ⊙ High performance, low power consumption
- ⊙ Read barcode symbology on phone screen
- ⊙ Read all major 1D and 2D barcode symbologies



Image Sensor	CMOS	Dimension	L × W × H: 171mm × 66mm × 86mm
Image size	648 × 488 pixels	Weight	130g
Light Source	Red light, LED	Material	ABS+PC
Precision	≥ 5mil	Voltage	DC 3.3V ± 5%
Depth of Scan Field	6-25cm (Code39, 15mil), 6-25cm (UPC/EAN, 15mil)	Current (Working)	135mA
Scensitivity	Roll: 360° Skew: ±65°, Pitch: ±60°	Operate Temperature	- 20°C to 60°C
Support Interface	USB and RS232	Storage Temperature	- 20°C to 60°C
Print Contrast Signal	≥ 30%	Humidity	5% to 95%
Indicator	Buzzer, LED	Illumination	0 to 100000LUX
Scan Mode	Manual & Automatic & Continuous	Certification	EC (EMC) Class B, RoHS
Decoding Capability	1D: EAN-8, EAN-13, UPC-A, UPC-E, Code39, Code93, Code128, EAN128, Codabar, Industrial 2 of 5, Interleave 2 of 5, Matrix 2 of 5, MSI, Chinese postcode etc. 2D: PDF417, QR Code (Mode/2), DataMatrix (ECC200, ECC000, 050, 080, 100, 140), etc.		



**SUNLUX IOT Technology (Guangdong) Inc.**

Office Add: 4F, No. 7, Kehui First Street, Science Road, Science City, Guangzhou, China

Tel: +86-20-32053765 Fax: +86-20-82115390 Site: [www.xl-scan.com](http://www.xl-scan.com) E-mail: [sales@xl-scan.com](mailto:sales@xl-scan.com)