

## DTW

## DTW "DUAL TRACK" VEHICLE WEIGHING SERIES




Innovative vehicle weighing dual track weighbridge, easily transportable and installable thanks to the reduced height and weight. Designed and built with vey high quality materials, this represents the most efficient solution for saving time, space, and money in comparison to the classic weighbridges currently available on the market. The standard version is fitted with CE-M 3000e APPROVAL, for legal for trade use.

### **TECHNICAL FEATURES**

- Precise and versatile platforms, suitable for all kinds of applications; ideal for modern industries, farms, work yards, landfills, ports, etc, in which one can save space or change the logistical stations.
- Extremely compact: only 22 cm high. Takes up little space if installed on the street surface, reduced masonry if installed flush floor to the road surface.
- The load capacity complies with the <u>96/53/EC Directive</u> which defines the maximum axle load for the vehicles transiting in Europe (version for higher loads is available upon request).
- Sturdy loading surface in striated sheet steel.
- Sandblasting and varnishing with bi-component epoxy coating, highly resistant to corrosion.
- Installable above, as well as flush floor to the street surface.
- Reinforced on and off ramps, for mobile or fixed installation (optional).
- Weight detection system through oscillating load bars (patented system) with integrated brake / acceleration compensating limits and anti-slip rubber resting plates.
- Load cells protected from dust and water.
- Fitted with approval, carried out in factory (to be combined with Dini Argeo indicator).
- Dust and waterproof wirings and connections, easy to connect and disconnect.
- Modularity: by adding or removing pairs of modules, the weighbridges can have these lengths: 4,5 m 9 m 13,5 m 18 m 22,5 (up to 36m by price estimate).
- Wide range of connectable weight indicators, also functioning with rechargeable battery, which allow to use the weighbridge also without an electrical power supply.
- 30m long connection cable between DTW and indicators.


### **OPTIONS AND ACCESSORIES**

- Available upon request with special capacities and divisions.
- Transport (upon price estimate).
- Kit of on/off mobile ramps.
- Angles of crest kit for flush floor installation or for concrete on/off ramps.
- Dual range CE-M 3000 + 3000e approved (upon price estimate).





# DETAIL 3



## **VERSIONS**

Available versions					
	l x w x h	Contenuto totale	Max	M	M
Codice	(m)	Contenuto totale	(kg)	(kg)	2R (kg)
DTW515A-8	2x (4,50x1,00x0,22)	2 bridges - 4 weighing bars	15000	5	
DTW530A-8	2x (4,50x1,00x0,22)	2 bridges - 4 weighing bars	30000	10	5/10(**)
DTW930A-8	2x (9,00x1,00x0,22)	4 bridges - 6 weighing bars	30000	10	5/10(**)
DTW960A-8	2x (9,00x1,00x0,22)	4 bridges - 6 weighing bars	60000	20	10/20(**)
DTW1430A-8	2x (13,50x1,00x0,22)	6 bridges - 8 weighing bars	30000	10	5/10(**)
DTW1460A-8	2x (13,50x1,00x0,22)	6 bridges - 8 weighing bars	60000	20	10/20(**)
DTW1860A-8	2x (18,00x1,00x0,22)	8 bridges - 10 weighing bars	60000	20	10/20(**)
DTW1880A-8	2x (18,00x1,00x0,22)	8 bridges - 10 weighing bars	80000	50	20/50(**)
DTW2280A-8	2x (22,50x1,00x0,22)	10 bridges - 12 weighing bars	80000	50	20/50(**)

<sup>(\*)</sup>NET PRICES: please contact the sales department for further information.

<sup>(\*\*)</sup> Fitted with CE-M 3000e approval. The dual range CE-M 3000  $\pm$  3000e approval is optional, upon price estimated.





DINI ARGEO FRANCE sarl France DINI ARGEO GMBH Germany DINI ARGEO UK Ltd United Kingdom DINI ARGEO WEIGHING INSTRUMENTS Ltd China DINI ARGEO OCEANIA Australia



#### **COMPANY HEADQUARTERS**

Via Della Fisica, 20 41042 Spezzano di Fiorano Modena • Italy Tel. +39.0536 843418

## CLAIRE AFRICA LTD

BLESSED HOUSE, 1ST FLOOR, NO. 15, THIKA - 600 - NAIROBI - KENYA Tel. (254) 777 601690

info@claire.co.ke

SALES AND TECHNICAL ASSISTANCE SERVICE