

3590EGT

3590EGT "GRAPHIC TOUCH": Touch Screen weight indicator for industrial applications



Digital weight indicator with a big touch screen display, suitable for advanced industrial applications. It allows the visualization of all the weighing data and the customization of the screens, simplifying the user operations. Fitted with 3 serial ports, transmission protocols for data communication, completely configurable printouts, integrated alibi memory, and port for connection to barcode/badge reader. CE-M approvable (OIML R-76 / EN 45501).

MAIN FEATURES

- Backlit graphic display with touch screen technology, lxh= 120x90mm size.
- Multilanguage software.
- 15-key alphanumerical waterproof keyboard.
- 3-way control light.
- Selectable QWERTY, AZERTY o QWERTZ keyboard integrated in the touch screen.
- Stainless steel waterproof IP68 enclosure, new optional IP69K protection system.
- Dimensions: 280x143x185 mm.
- Suitable for use on the table, column, or wall.
- Real time clock and permanent data storage.
- Supplied with alibi memory, integrated on the motherboard.
- Slot for built-in micro SD for recording the configuration, logos, and customized screens (upon request).
- Functions available with DINITOOLS utility
 - Configuration, data entry and print formatting.
 - Recording and filing of all the information on PC.
 - Complete retrieval of the configuration.
 - Instrument calibration with numeric values.
 - Customization of the screens.
- 24-bit A/D converter, 4 channels, up to 3200 conv./sec. and up to 8 signal linearisation points.
- 4 independent analogue channels (up to 2 in the E-AF03 version) for reading of the weight.
- Connection with up to 16 analogue load cells of 350 Ohm (45 load cells of 1000 Ohm) and with the main digital load cells available on the market (mod. E-AF03).
- Management of the most common digital load cells for weigh bridges (with DIGIKIT option and AF03GT firmware), also for applications with CE-M approval.
- Up to 10.000e OIML or 3 x 3000e @ 0,3 μV/e CE-M legal for trade.
- Up to 1.000.000 displayable divisions for internal factory use, with internal resolution up to 3.000.000 points.
- Connectable to printers and labellers with free programmation of the printout formats.
- 110-240 Vac power supply.

MAIN CERTIFICATIONS

- EU Type Examination Certificate (45501:2015)
- OIML R76
- OIML R51 MID
- OIML R134 (AF09)

APPLICATION SOFTWARE

- AF01: Totalization and formula weighing (integrated)
- AF02: Pieces/quantity counting (optional)
- AF03: Weighbridges Input/Output vehicle (optional)
- AF04: Statistical checking of prepackaged goods (optional)
- AF05: Price compunting and industrial labelling (optional)
- AF08: Wheel and axle static weighing with 2 or various platforms (optional)
- AF09: Software for dynamic and static axle weighing with 1 or 2 platforms (optional)
- BATCH1: Single product dosage systems in loading and unloading (optional)
- BATCH: Software for multicomponent dosage systems in loading and unloading (optional, IOEXPB board must be included)

CUSTOMISED APPLICATIONS

Thanks to our integrated development, you can create complete customised applications in autonomy:

- · wizards, operator messages
- serial port management, protocols customization
- digital I/O full management
- sequential or simultaneous automations
- · data entry, custom archives

Dini Argeo can offer the service of custom development programs.

IDEAL FOR DIGITAL APPROVED WEIGHBRIDGES

• The 3590EGT indicator with the AF03GT firmware manages the most common digital load cells for weigh bridges, even for CE-M approved applications:

Dini Argeo RCPTD

Dini Argeo RCD

Rice Lake RL5416D/RL5426D

Sensocar SP/CS

Scaime CB50X-DL

Flintec RC3D

HBM C16i (requires HBM junction box and RS422 converter\RS485)

Zemic DM-B4110, DM-B4310, DM-B4311, DM-E5310

For a complete list of supported load cells, refer to the AF03GT Weighing Program Technical Manual.

For efficient handling and optimal protection of digital load cells, the use of the DIGIKIT option is reccommended.

DETAIL 1 DETAIL 2





3590EGT with IP65 INOX printer





DINI ARGEO FRANCE sarl France DINI ARGEO GMBH Germany DINI ARGEO UK Ltd United Kingdom DINI ARGEO WEIGHING INSTRUMENTS Ltd China DINI ARGEO OCEANIA Australia



COMPANY HEADQUARTERS

Via Della Fisica, 20 41042 Spezzano di Fiorano Modena • Italy Tel. +39.0536 843418

CLAIRE AFRICA LTD

BLESSED HOUSE, 1ST FLOOR, NO. 15, THIKA - 600 - NAIROBI - KENYA Tel. (254) 777 601690

info@claire.co.ke

SALES AND TECHNICAL ASSISTANCE SERVICE