

PB

"PB" SERIES SINGLE CELL PLATFORMS



Small and medium capacity electronic platforms with a stainless steel surface having a precise and sturdy structure.

- Up to 15000d resolution.
- OIML R60 C3.
- IP65 protection.


TECHNICAL FEATURES

- Optional calibration service from 6000d to 15000d (internal use); 3000e approved OIML R60 C3.
- Functioning with a "single point" 350 Ohm aluminium load cell, IP65 protection degree.
- Steel tubular structure, oven-fire painted blue, with adjustable resting feet and level.
- Fitted with stainless steel loading surface.
- Up to 15 Vdc power supply.
- 3m shielded cable for connection to the indicator.
- Upon request:
 - 3000e CE-M approval;
 - support column for indicator.

SUPPORT BRACKETS AND COLUMNS

• Example of use with bracket, attached column or floor column.





Available versions					
	l x w x h	Max	d	M	d HR
Codice	(mm)	(kg)	(g)	(g)*	(g)*
PBT6	300x300x130	6	1	2	0,5
PBT15	300x300x130	15	2	5	1
PBT30	300x300x130	30	5	10	2
PBQ30	400x400x140	30	5	10	2
PBQ60	400x400x140	60	10	20	5
PBQ150	400x400x140	150	20	50	10
PBM30	400x500x140	30	5	10	2
PBM60	400x500x140	60	10	20	5
PBM150	400x500x140	150	20	50	10
PBX60	600x600x150	60	10	20	5
PBX150	600x600x150	150	20	50	10
PBX300	600x600x150	300	50	100	20
PBY60	600x800x150	60	10	20	5
PBY150	600x800x150	150	20	50	10
PBY300	600x800x150	300	50	100	20
PBE300	800x800x165	300	50	100	20
PBE600	800x800x165	600	100	200	50

^(*) Divisions obtainable only with the relative options, in combination with Dini Argeo weight indicator.





DINI ARGEO FRANCE sarl France DINI ARGEO GMBH Germany DINI ARGEO UK Ltd United Kingdom DINI ARGEO WEIGHING INSTRUMENTS Ltd China DINI ARGEO OCEANIA Australia



COMPANY HEADQUARTERS

Via Della Fisica, 20 41042 Spezzano di Fiorano Modena - Italy Tel. +39.0536 843418

CLAIRE AFRICA LTD

BLESSED HOUSE, 1ST FLOOR, NO. 15, THIKA - 600 - NAIROBI - KENYA Tel. (254) 777 601690

info@claire.co.ke

SALES AND TECHNICAL ASSISTANCE SERVICE